



CINEMA SUB

Product sheet

MADE IN
FRANCE

The UTOPIA CINEMA line embodies Focal's unique expertise. Designed for private cinema rooms of up to 2153 square feet (200m²), it incorporates speaker drivers from our highest-quality monitors, Utopia Main, for an uncompromising sound experience where every single sound detail is enhanced. Within the range, CINEMA SUB symbolises Utopia excellence. With its high SPL capacity, this subwoofer guarantees unparalleled power and precision in the sub-bass.




Key points

- Bass-reflex subwoofer designed for bass frequencies
- Option to combine as many Cinema SUB and Cinema LCR loudspeakers as desired
- Speaker drivers developed and manufactured in France by Focal
- The brand's Utopia signature
- Mounted onto or into the wall, with modular configurations
- High power handling suitable for large private cinema rooms
- Supplied with a grille


Specifications

Type	Subwoofer bass-reflex In-wall / On-wall / Freestanding
Tuned port	19Hz
Speaker drivers	2x13" 'W' cone woofers
Sensivity (2.83V/3feet - 1m)	95dB (66Hz)
Bandwidth (-3dB) 2Pi	42Hz - 2500Hz
Low-frequency cut-off (-10dB)	19Hz - 2500Hz
Recommanded EQ	19Hz - 2500Hz ± 1 dB +12dB @20Hz Q=1.8 and shelving -5dB @50Hz (1 st order) and 24 dB/oct @18Hz butterworth
Nominal impedance	5 Ω
Minimal impedance	4.1 Ω to 19Hz
Crossover	No
Rated power	300W RMS (4 Ω)
Recommended amp power	Max 400W (8 Ω) / Max 800W (4 Ω)
Dimensions (HxWxD)	45 ^{7/8"} x21 ^{5/8"} x12 ^{13/16"} (116.5x54.9x32.6cm)
Net weight	160.94lbs (73kg)

DIMENSIONS



FREQUENCY RESPONSE



LEVELS CALCULATION TABLE

CINEMA SUB (2Pi) @66Hz				95dB			
Power (8Ω) / Distance	1m	2m	5m	10m			
1W (4Ω) (2.83V)	95dB	89dB	81dB	75dB			
50W (4Ω) (20V)	112dB	106dB	98dB	92dB			
100W (4Ω) (28.3V)	115dB	109dB	101dB	95dB			
500W (4Ω) (44.7V)	122dB	116dB	108dB	102dB			
800W (4Ω) (63.2V)	124dB	118dB	110dB	104dB			
Summary	20Hz	34Hz	66Hz	80Hz	110Hz	200Hz	2kHz
NPA (2.83V) / 1m (dB)	85	90	95	96	97	98	98

CINEMA SUB (2Pi) @34Hz				90dB			
Power (8Ω) / Distance	1m	2m	5m	10m			
1W (4Ω) (2.83V)	90dB	84dB	76dB	70dB			
50W (4Ω) (20V)	107dB	101dB	93dB	87dB			
100W (4Ω) (28.3V)	110dB	104dB	96dB	90dB			
500W (4Ω) (44.7V)	117dB	111dB	103dB	97dB			
800W (4Ω) (63.2V)	119dB	113dB	105dB	99dB			

CINEMA SUB (2Pi) @20Hz				85dB			
Power (8Ω) / Distance	1m	2m	5m	10m			
1W (4Ω) (2.83V)	85dB	79dB	71dB	65dB			
50W (4Ω) (20V)	102dB	96dB	88dB	82dB			
100W (4Ω) (28.3V)	105dB	99dB	91dB	85dB			
500W (4Ω) (44.7V)	112dB	106dB	98dB	92dB			
800W (4Ω) (63.2V)	114dB	108dB	100dB	94dB			

2x CINEMA SUB (2Pi) @20Hz				91dB			
Power (8Ω) / Distance	1m	2m	5m	10m			
1W (4Ω) (2.83V)	91dB	85dB	77dB	71dB			
50W (4Ω) (20V)	108dB	102dB	94dB	88dB			
100W (4Ω) (28.3V)	111dB	105dB	97dB	91dB			
500W (4Ω) (44.7V)	118dB	112dB	104dB	98dB			
800W (4Ω) (63.2V)	120dB	114dB	106dB	100dB			

3x CINEMA SUB (2Pi) @20Hz				94dB			
Power (8Ω) / Distance	1m	2m	5m	10m			
1W (4Ω) (2.83V)	94dB	88dB	80dB	74dB			
50W (4Ω) (20V)	111dB	105dB	97dB	91dB			
100W (4Ω) (28.3V)	114dB	108dB	100dB	94dB			
500W (4Ω) (44.7V)	121dB	115dB	107dB	101dB			
800W (4Ω) (63.2V)	123dB	117dB	109dB	103dB			

4x CINEMA SUB (2Pi) @20Hz

97dB

Power (8Ω) / Distance	1m	2m	5m	10m
1W (4Ω) (2.83V)	97dB	91dB	83dB	77dB
50W (4Ω) (20V)	114dB	108dB	100dB	94dB
100W (4Ω) (28.3V)	117dB	111dB	103dB	97dB
500W (4Ω) (44.7V)	124dB	118dB	110dB	104dB
800W (4Ω) (63.2V)	126dB	120dB	112dB	106dB

8x CINEMA SUB (2Pi) @20Hz

103dB

Power (8Ω) / Distance	1m	2m	5m	10m
1W (4Ω) (2.83V)	103dB	97dB	89dB	83dB
50W (4Ω) (20V)	120dB	114dB	106dB	100dB
100W (4Ω) (28.3V)	123dB	117dB	109dB	103dB
500W (4Ω) (44.7V)	130dB	124dB	116dB	110dB
800W (4Ω) (63.2V)	132dB	126dB	118dB	112dB

16x CINEMA SUB (2Pi) @20Hz

109dB

Power (8Ω) / Distance	1m	2m	5m	10m
1W (4Ω) (2.83V)	109dB	103dB	95dB	89dB
50W (4Ω) (20V)	126dB	120dB	112dB	106dB
100W (4Ω) (28.3V)	129dB	123dB	115dB	109dB
500W (4Ω) (44.7V)	136dB	130dB	122dB	116dB
800W (4Ω) (63.2V)	138dB	132dB	124dB	118dB